

SHELVING

PARTICLEBOARD
MDF



Add some practical storage practically anywhere.

Homeowners can never get enough storage. That's what makes Temple-Inland® shelving so appealing. Precut in three popular widths and four lengths, it is designed for compatibility with a wide range of easily available shelf brackets and supports. Our shelving is manufactured with either Temple-Inland MDF or particleboard and is produced raw, ideal for painting or laminating. Square or bull nosed, it is cost efficient, easy to install and durable. So whether it's in the pantry, garage, bedroom or study, Temple-Inland shelving makes it easy to add practical storage solutions practically anywhere.

Temple-Inland®

Core Material

Available with either a strong, durable particleboard or MDF substrate to match a variety of applications and performance requirements.

Span Chart

To determine the uniform load in pounds per square foot, convert the square inches of the shelf to square feet by dividing by 144" (one square foot). Then, divide the expected load by the answer and you will get the uniform load.

SPAN CHART			
Maximum shelf spans in inches for uniform loading of 3/4" thick shelves			
	End Supported	Multiple Supports	Overhanging Shelf
	Span		Overhang
Load*	Maximum Span	Maximum Span	Maximum Overhang
50.0	23	31	11
45.0	24	32	11
40.0	25	34	12
35.0	26	35	12
30.0	27	37	13
25.0	29	39	13
20.0	31	42	14
17.5	32	43	15
15.0	34	45	16
12.5	35	48	16
10.0	38	50	17
7.5	40	54	19
5.0	44	60	21

*load in pounds per square foot

Compliances

Temple-Inland shelving conforms to the Composite Panel Association guidelines when installed according to this span chart.

Temple-Inland

www.templeinland.com | 800-231-6060

© 2009 TIN, Inc. Temple-Inland is a trademark of TIN, Inc. CS 17412 06/09



Available raw, our shelving is ready to paint or laminate and install.

PRODUCT DIMENSIONS

Thickness:	3/4"
Lengths:	4', 6', 8', 12'
Widths:	12", 16", 24" (NOMINAL)*
Edge:	SQUARE AND BULL NOSED

*actual sizes are 1/2" under, custom sizes available with appropriate lead time and volume.

Storage

Store engineered wood shelving flat, in a dry location and avoid direct contact with the ground.

Shipping Information

Unitized and strapped to risers and protected from strapping damage. Shipments may be made in truck or rail

Recycled Content Certification:

Scientific Certification Systems (SCS) has awarded certification to Temple-Inland's El Dorado, Arkansas MDF plants for producing products using recovered and recycled materials.



UltraStock Select, Premium and Lite MDF produced in Temple-Inland's El Dorado, Arkansas facility is certified to contain 80% pre-consumer recycled fiber on a dry fiber weight basis.

The UltraStock Select and Premium MDF produced in Temple-Inland's Mt. Jewett, Pennsylvania facility is available on special order with a Composite Panel Association's certification of compliance to the Environmentally Preferable Product (EPP) specification standard CPA 2-06 verifying a recycled and/or recovered fibers content of 100%.



Available by request.