

Product Description

Regular Fiberboard Wall Sheathing is a medium-density cellulosic fiber insulating board that is an ideal backer for all siding materials such as vinyl, hardboard and fiber cement. Regular Sheathing also delivers added thermal insulation, sound-deadening qualities, and moisture permeability. Plus, its asphalt coating increases the wall structure’s resistance to moisture and air infiltration.

Advantages

- Can be used all around structure when required bracing is provided by other means.
- Provides added insulation with an R-Value of 1.31.
- Effectively muffles exterior noise twice as well as plywood.
- Increases wall cavity resistance to moisture damage via high water vapor permeability.
- Its asphalt coating deflects water infiltration and minimizes moisture absorption.
- Has a sound transmission class 26 (ASTM Method E90).
- Scientific Certification Systems (SCS) certified to contain at least 84% recycled pre-consumer wood fiber on a dry weight basis.
- Manufactured with no-added urea formaldehyde.

Limitations

- Regular Sheathing should not be used as a base for any mechanical fastening including nailing.
- Avoid exposure to constant moisture before, during and after installation.
- Should not be applied below grade.
- Do not use for floor or roof applications.

Applicable Standards

- Meets or exceeds the requirements in the building code-referenced industry standard ASTM C208, the Specification for Cellulosic Fiber Insulating Board.
- Complies with and recognized by the International Residential Code (IRC) and the International Building Code (IBC).
- International Code Council Evaluation Report (ICC-ESR 1519).
- Classified as a Type IV (wall sheathing), Grade 1 building panel.
- Certified and labeled by the American Fiberboard Association, an IAS-accredited third-party certification organization.

Submittal Approvals

JOB NAME: _____

CONTRACTOR: _____ DATE: _____

Product Data

WIDTH	LENGTH	THICKNESS	PRODUCT WEIGHT
4'	8' & 9'	½"	840 lbs/msf

