

Product Description

Temple-Inland® regular gypsum board is designed as an economical and aesthetically pleasing covering for walls and ceilings which accepts paint, wallpaper, paneling and many other surface treatments. This product is available in various thicknesses to cover a wide variety of applications. The long edges are tapered to allow joints to be concealed and finished to provide a smooth, monolithic surface.

- ¼" A lightweight, low-cost gypsum board used to form curved surfaces, cover old wall and ceiling surfaces, and as a base layer for improving sound control in double layer steel and wood stud partitions.
- ⅜" A lightweight, low-cost gypsum board used in double wall systems over wood framing. Also used for repair and remodeling of residential and commercial construction.
- ½" A lightweight, low-cost gypsum board used extensively in residential construction.

Advantages

- Lightweight, easy-to-install, cost-efficient material that accepts a wide range of finishes
- May be installed over wood or metal framing
- Panels do not support combustion
- Available with a minimum of 98% certified recycled content on a dry weight basis in accordance with ISO 14021 standards¹

Limitations

- Designed for interior use only
- Avoid exposure to prolonged, excessive temperatures: 125°F (52°C)
- Avoid exposure to excessive or continuous moisture
- Must be protected from direct exposure to weather and properly supported to prevent sag
- Should be stored, handled and installed to comply with industry standards GA216 & ASTM C840

Applicable Standards

- Meets or exceeds ASTM C1396
- Federal Specification SS-L-30D, Type III & Grade R
- Installation Standards ASTM C840, GA214 & GA216
- Surface Burning Characteristics ASTM E-84 Flame Spread 15 Smoke Developed 0

Submittal Approvals

JOB NAME: _____

CONTRACTOR: _____ DATE: _____

Product Data

WIDTH	LENGTH	THICKNESS / PRODUCT WEIGHT
4' (1219mm) 4.5' (1371mm) (Stretch54®)	8' to 16' (2438mm to 3658mm)	¼" (6.35mm) Reg, 1.2 lbs/ft² ⅜" (9.53mm) Reg, 1.4 lbs/ft² ½" (12.7mm) Reg, 1.6 lbs/ft²

Special Order Information: Other widths, edges and lengths may be available on special order with established minimums and lead time. Some products may not be available in all markets. Please check with your local Temple-Inland sales representative.

1. The recycled content levels of board produced at our Cumberland City, Tennessee, Fletcher, Oklahoma, and West Memphis, Arkansas, facilities are third-party verified by Scientific Certification Systems (SCS).

