

Product Description

Temple-Inland® SilentGuard™ shaftliner is a fire-resistant 1"-thick by 2'-wide gypsum board designed for use in stairwells, elevator shafts and area separation walls. The front and back facers are tinted green to indicate their water resistant properties.

Advantages

- Edges are double beveled for ease of installation into metal framing
- Lightweight and cost effective
- Fire resistance classified by Underwriters Laboratories according to ASTM E119
- Allows wall construction from only one side of wall
- Available with a minimum of 93% certified recycled content on a dry weight basis in accordance with ISO 14021 standards¹

Limitations

- For use only in non-load bearing assemblies
- Avoid exposure to prolonged, excessive temperatures: 125°F (52°C)
- Avoid exposure to excessive or continuous moisture

Applicable Standards

- Meets or exceeds ASTM C1396
- Federal Specification SS-L-30D, Type IV & Grade X

Submittal Approvals

JOB NAME: _____

CONTRACTOR: _____ DATE: _____

Product Data

WIDTH	LENGTH	THICKNESS / PRODUCT WEIGHT
2' (609.6mm)	8' to 12' (2438mm to 3658mm)	1" (25.4mm) 4.0 lbs/ft ²

Special Order Information: Other widths, edges and lengths may be available on special order with established minimums and lead time. Some products may not be available in all markets. Please check with your local Temple-Inland sales representative.

1. The recycled content levels of board produced at our Cumberland City, Tennessee, Fletcher, Oklahoma, and West Memphis, Arkansas, facilities are third-party verified by Scientific Certification Systems (SCS).

