

Product Description

SoundChoice® Sound-Deadening Fiberboard is a low-density cellulosic fiber panel that provides an outstanding barrier to the transmission of unwanted noise vibrations. It is suitable for use in construction of interior and exterior walls as well as floors and ceilings. It even provides an additional boost to the R-value of an assembly and is available in 1/2"-thick 4' x 8' sheets.

Advantages

- Provides a noise reduction coefficient of 0.35 (ASTM Method C423).
- Sound transmission class 26 (ASTM Method E90).
- Provides thermal insulation with an R-Value of 1.22 (ASTM Method C518).
- Lightweight and rigid for trouble-free handling and installation.
- Easy to cut and fasten.
- Suitable for use in a wide range of wall and floor-ceiling assemblies to deliver multiple levels of sound reduction.
- Scientific Certification Systems (SCS) certified to contain at least 97% recycled pre-consumer wood fiber on a dry weight basis.
- Manufactured with no-added urea formaldehyde.

Limitations

- Do not expose to an open flame.
- Do not expose to prolonged excessive heat above 212°F without sufficient thermal protection.
- Do not use as a nail base for other materials.

Applicable Standards

- SoundChoice is certified by a third-party agency as meeting the requirements of ASTM C208, the Standard Specification for Cellulosic Fiber Insulation Board, as a Type I sound-deadening board.
- International Code Council Evaluation Report (ICC-ESR 1519).

Submittal Approvals

JOB NAME: _____

CONTRACTOR: _____ DATE: _____

Product Data

WIDTH	LENGTH	THICKNESS	PRODUCT WEIGHT
4'	8'	1/2"	715 lbs/msf

