

**Product Description**

Temple-Inland® Span24™ is a specially formulated 1/2"-thick gypsum board designed to be installed on ceilings with 2' framing spacing. This special gypsum board exceeds the sag requirement of 5/8" gypsum board, which makes its application less expensive and lighter weight.

**Advantages**

- Lower cost and lighter weight than 5/8" gypsum board
- Meets or exceeds sag requirements of 5/8" gypsum board
- Less waste on the job site since 1/2" Span24 may also be used on walls
- Available with a minimum of 93% certified recycled content on a dry weight basis in accordance with ISO 14021 standards<sup>1</sup>

**Limitations**

- This product must be installed perpendicular to framing
- Framing spacing not to exceed 24"
- Provide adequate ventilation when applying texture to this product
- Should be stored, handled and installed to comply with industry standards GA216 & ASTM C840

**Applicable Standards**

- Meets or exceeds ASTM C1396
- Federal Specification SS-L-30D, Type III & Grade R
- Application Standards ASTM C840, GA214 & GA216
- Surface Burning Characteristics ASTM E-84 Flame Spread 15 Smoke Developed 0

**Submittal Approvals**

JOB NAME: \_\_\_\_\_

CONTRACTOR: \_\_\_\_\_ DATE: \_\_\_\_\_

**Product Data**

WIDTH	LENGTH	THICKNESS / PRODUCT WEIGHT
4' (1219mm)	8' to 12' (2438mm to 3658mm)	1/2" (12.7mm) 1.7 lbs/ft <sup>2</sup>

**Special Order Information:** Other widths, edges and lengths may be available on special order with established minimums and lead time. Some products may not be available in all markets. Please check with your local Temple-Inland sales representative.

1. The recycled content levels of board produced at our Cumberland City, Tennessee, Fletcher, Oklahoma, and West Memphis, Arkansas, facilities are third-party verified by Scientific Certification Systems (SCS).

